### LIFTING TECHNOLOGY

## MOBILE COLUMN LIFT







#### **RGE** VP 451065

The mobile wheel engaging COLUMNLIFT RGE lifts up to 7.5 t per column. Streamline column design offers a good overview when manoeuvring. The low-maintenance, electro-mechanical drive system ensures extremely smooth running while the excellent mechanical rigidity of the columns guarantees safety and the ability to function in any condition. A high-quality worm gear motor enables precision height positioning without overrun. Column communication is via connecting cable, the power supply via mains power.

#### PRODUCT DETAILS/ACCESSORIES

- · Very smooth running due to electro-mechanical drive system
- High efficiency thanks to smooth-running, low-maintenance hall screw
- · 5-year warrantee for entire spindle drive
- Excellent lifting column mechanical rigidity guarantees safety and function under any conditions
- Precision-height positioning without overrun thanks to highquality worm gear motor
- Lifting carriages with fixed holder
- Overhead drive unit creates even more space in the work area
- Workshop-robust and splash-proof control unit
- Wear-free and easy-to-use membrane keypad
- Flexible column positioning thanks to excess-length connection cables, guaranteeing suitability across all vehicle categories
- User convenience with panel operator controls on each individual column
- · High level of flexibility in use due to different operating modes
- Group and individual column operating modes enable quick

- and easy replacement of wheel and axle suspensions
- Microprocessor control and CAN bus-supported monitoring of movement synchronisation and all safety functions
- Utmost safety thanks to mechanically independent locking device
- Simple emergency lowering for power failure included as standard
- · System can easily be expanded with up to six columns
- Streamline COLUMNLIFT design aids manoeuvrability specifically in workstations with restricted space
- · High-quality powder coating:
  - Window Grey, RAL 7040 (Columns)
  - Anthracite, Grey RAL 7016 (Lifting carriages)

#### Scope of delivery:

- 4 individual mobile columns
- 3 connecting cables (10m each) with plug and socket
- 1 mechanical dolly, repositionable

#### **TECHNICAL DATA**

Load capacity CE per column	7500 kg
Drive power per column	1.5 kW
Weight per column	452 kg
Lifting distance	1750 mm
Raising/lowering time	113 s
Tyre diameter min max.	850 - 1250 mm
Supply voltage	3/N/PE 400 V 50 Hz
Protection rating	IP 54

#### **ACCESSORIES**

VZ 971260	Single RGE Post (MAHA), 7500 kg lifting capacity incl. connection cable & plug	VP 451073	Single RGE Post (MAHA) -SUBSEQUENT DELIVERY Lifting capacity 7500 kg
VZ 971204	Special Control Unit for connection of up to 12 wheel grabbing posts -EXTRA CHARGE-	VZ 971159	Power Unit 3 x 400V/50Hz
		VZ 971323	Lifting Carriage with Fixed Wheel Grabbers for
			special tyres up to 14.00x25

# LIFTING TECHNOLOGY MOBILE COLUMN LIFT





VZ 971322 VZ 971281	Insertion Paws EP 6 for Small Tires (2 pcs.) RGE Lift to be used in Wash Halls -EXTRA		VZ 971290	Support Plate APVV II -Squareadjustable, for Support Stand AB 6-07/12/20
12 37 120 1	CHARGE PER POST-		VZ 971168	Screw Adjustment SP 75 for AB 6-07/12/20
VZ 971182			Support Stands	
	with emergency stop switch		VZ 971310	Crossbar for Support of SemiTrailers with 2 King
VZ 971179	Removable Mechanical Dolly, MODEL: MFR-2		\	Pin Table 201   1   1   2
VZ 971181	Hydraulic Pallet-Type Fixed Dolly, screwed onto	VZ 971546	Transverse Beam TR8 32 Load capacity 8t	
	post MODEL: MFP		VZ 971347	Transverse Beam TR10-32 Load capacity 10t
VZ 971305	Insertion Paws EP 5 Wheel for Small Tires (2 pcs.)		VZ 990314	Special Voltage (RGE) 3x230 V, 50 Hz/60 Hz a
VZ 971164	Support Stand AB 6-07, lifting capacity 7500 kg,		maximum of 6 posts possible	
	adjustment range 470 - 795 mm (each)		VZ 990456	Linking cable 15 m -Extra charge per cable
VZ 971165	Support Stand AB 6-12, lifting capacity 7500 kg,	VZ 990457	Linking cable 20 m -Extra charge per cable	
	adjustment range 875 - 1395 mm, mobile		SUPPLEMENTARY CHARGES	
VZ 971166	Support Stand AB 6-20, lifting capacity 7500 kg, adjustment range 1200-1965 mm, mobile		VT 998032	Transportkosten 2 Einzelsäulen inkl. Verpackung
VZ 971287	Support Plate APR II -Roundpluggable, for Support Stand AB 6-07/12/20	VT 995698	Transportkosten 4 Einzelsäulen inkl. Verpackung	
V 2 37 1207		VT 995699	Transportkosten 6 Einzelsäulen inkl. Verpackung	
VZ 971288		VT 995703	Transportkosten 8 Einzelsäulen inkl. Verpackung	
		VT 995704	Transportkosten 10 Einzelsäulen inkl. Verpackung	
VZ 971289	Support Plate APV II -Squarefor Support Stand AB 6-07/12/20	VT 995705	Transportkosten 12 Einzelsäulen inkl. Verpackung	
		VM 996077	Installation costs for mobile column lifts	
			VV 997560	Transport cradle for mobile columns (horizontal) each containing 2 columns