PERFORMANCE MEASUREMENT TECHNOLOGY ASM

ASM-P-PLUS VP 230047





ACCESSORIES

| VZ 910167 | USB/RS 232 Converter for Connection to PC/ Laptop w/o. RS 232 Interface -NET- |
|-----------|--|
| VZ 975081 | Side-Restraining Rollers (2 pcs.) |
| VZ 935288 | Lashing Straps with Floor Anchor |
| VZ 911224 | ASM-P Software Module Standard Power Measurement |

ASM-P-PLUS VP 230047

The ASM-P-PLUS roller set is used in test centres and is suitable for vehicles with a single driven axle. It was designed for the exact measurement of the exhaust gas behaviour of vehicles during their transient emission test and permits a driving resistance simulation for the exhaust gas tests ASM-5015 and ASM-2525 (Acceleration Simulation Mode) in accordance with the specifications BAR '97. The increased tractive force of its eddy current brake means that the ASM-P-PLUS is also suitable for power measurements at constant speed and constant tractive force.

| VZ 973097 Galibration Device ASIVI AL/DI | VZ 975897 | Calibration | Device | ASM | AF/BF |
|--|-----------|-------------|--------|-----|-------|
|--|-----------|-------------|--------|-----|-------|

SUPPLEMENTARY CHARGES

VT 998137 Transportkosten für ASM

- VM 995010 Assembly costs after expenditure of time by hour.
- VV 997554 Packaging charges for Adjusting device